

Product Specifications

Model	Type	Impedance (Ohms)	Power Cont / Peak	MAX SPL Cont / Peak	Freq Resp (-3dB)	Dispersion	Weight (kgs)	Dimensions H x W x D (mm)
-------	------	------------------	-------------------	---------------------	------------------	------------	--------------	---------------------------

Installation

CT-6	Mid-high	16	150 / 600 W	108 / 114 dB	87Hz - 17 kHz	100° x 40°	4	300 x 190 x 185
CT-26	Mid-high	8	250 / 1000 W	114 / 120 dB	90Hz - 17 kHz	100° x 40°	7	460 x 190 x 185
CW-26	Mid-high	8	250 / 1000 W	114 / 120 dB	85Hz - 18.5 kHz	120° x 40°	12	200 x 460 x 255
CW-28	Full range	8	400 / 1600 W	122 / 128 dB	65Hz - 18.5 kHz	160° x 40°	21	350 x 460 x 360
CT-10	Full Range	8	300 / 1200 W	123 / 129 dB	70 Hz - 19 kHz	90° x 40°***	19	570 x 320 x 260
CT-12	Full Range	8	450 / 1800 W	129 / 135 dB	55 Hz - 20 kHz	60° x 40°***	28	720 x 380 x 320
CT-15	Full Range	8	600 / 2400 W	130 / 136 dB	45 Hz - 20 kHz	60° x 40°***	38	800 x 450 x 430
CS-208	Subwoofer	8	250 / 1000 W	122 / 128 dB	55 Hz - 130 Hz	Omni	20	259 x 600 x 450
CS-212	Subwoofer	4	400 / 1600 W	125 / 131 dB	50 Hz - 110 Hz	Omni	35	350 x 790 x 550
CS-15	Subwoofer	8	400 / 1600 W	126 / 132 dB	50 Hz - 120 Hz	Omni	32	475 x 475 x 500
CS-18	Subwoofer	8	800 / 3200 W	131 / 137 dB	45 Hz - 130 Hz	Omni	48	576 x 576 x 600
CS-18H	Subwoofer	8	700 / 2800 W	133 / 139 dB	45 Hz - 120 Hz	Omni	72	1156 x 576 x 746
CS-218	Subwoofer	4	1400 / 5600 W	135 / 141 dB	37 Hz - 120 Hz	Omni	89	1156 x 576 x 746

Commercial

OS-12	Full range	8	200 / 800 W	98 / 104 dB	65 Hz - 16 kHz	360° x 140°	17.5	Ø520 x 520
CL-0T	Full range	8	6 / 24 W	87 / 97 dB	110 Hz - 20 kHz	140° Conical	0.42	Ø103 x 80
CL-1T	Full range	8	15 / 60 W	88 / 102.5 dB	80 Hz - 20 kHz	140° Conical	0.9	Ø203 x 86
CL-3T	Full range	8	20 / 80 W	90 / 106 dB	60 Hz - 20 kHz	140° Conical	1.4	Ø273 x 100
CL-1TD	Full range	8	15 / 60 W	88 / 102 dB	150 Hz - 20 kHz	140° Conical	1.7	Ø203 x 145
CL-2TD	Full range	8	30 / 120 W	88 / 105 dB	90 Hz - 20 kHz	140° Conical	2.2	Ø230 x 150
CL-3TD	Full range	8	40 / 160 W	88 / 106 dB	50 Hz - 20 kHz	140° Conical	3.1	Ø270 x 185
CL-SUB	Subwoofer	8	50 / 200 W	92 / 111 dB	40 Hz - 200 Hz	Omni	4	Ø280 x 192
AS-5	Full Range	8	30 / 120 W	103 / 109 dB	95 Hz - 19 kHz	90° Conical	3.5	210 x 280 x 148.5
AS-8	Full Range	8	65 / 260 W	109 / 115 dB	65 Hz - 19 kHz	90° Conical	5.5	284 x 375 x 215
VLA	Mid High	4	200 / 800 W	121 / 127 dB	155 Hz - 11 kHz	10° x 120°	13	1000 x 160 x 160
BootiQue	Satellite	16	50 / 200 W	106 / 112 dB	150 Hz - 20 kHz	90° x 90°	1.75	140 x 140 x 132

Active Cabinets

Active Model	Type	Power Peak (dB)	MAX SPL Peak	Freq Resp (-3dB)	Dispersion	Weight (kgs)	Dimensions H x W x D (mm)
BootiQue	Satellite (4 Ohm)	20 W	110 dB	38 Hz-20 kHz	90° x 90°	1.75	140 x 140 x 132
BootiQue	Bass	180 W	115 dB		Omni	27	340 x 330 x 500
BootiQue	Output	2 x 85 W @ 4 Ohm	-	48 Hz - 150 Hz		Omni	38
AS-B	Subwoofer	300 W	123 dB				
AS-B	Output	2 x 200 W @ 4 Ohm	-				



quick guide

Model	Type	Impedance (Ohms)	Power Cont / Peak	MAX SPL Cont / Peak	Freq Resp (-3dB)	Dispersion	Weight (kgs)	Dimensions H x W x D (mm)
-------	------	------------------	-------------------	---------------------	------------------	------------	--------------	---------------------------

Live Sound

HD-BB	Subwoofer	2 x 4	2 x 1500 / 2 x 6000 W	138 / 144 dB	37 Hz - 130 kHz	Omni	134	1156 x 578 x 856	
HD-MH	Mid-high	HF	16	80 / 320 W	136 / 142 dB	90 Hz - 23 kHz	40° x 20°	89	1156 x 576 x 746
HD-MH		Mid	16	160 / 640 W					
HD-MH		LF	4	500 / 2000 W					
MX-12	Full Range	HF	16	80 / 320 W	125 / 131 dB	75 Hz - 20 kHz	60° Conical	18.5	334 x 500 x 451
		LF	8	500 / 2000 W					
MX-15	Full Range	HF	16	80 / 320 W	125 / 131 dB	65 Hz - 20 kHz	60° Conical	20	371 x 500 x 511
		LF	8	500 / 2000 W					
Ersa Minor	Full Range	HF	16	100 / 400 W	127 / 123 dB	125 Hz - 20 kHz	120° Vertical	10	189 x 410 x 184
		Mid	32	250 / 1000 W					
Vela	Full Range	HF	32	100 / 400 W	130 / 136 dB	55 Hz - 20 kHz	100° Horizontal Vertical *	23.1	576 x 250 x 300
		LF		400 / 1600 W					
Ersa Major	Full Range	HF	16	80 / 320 W	137 / 143 dB	100 Hz - 20 kHz	120° x 10°	46	700 x 300 x 650
		Mid		160 / 640 W					
		LF		500 / 2000 W					
TRS-112	Full range	8	300 / 1200 W	124 / 130 dB	83 Hz - 19 kHz	90° x 40°	24	575 x 398 x 295	
TRS-115	Full range	8	500 / 2000 W	127 / 133 dB	85 Hz - 19 kHz	60° x 40°	36	700 x 506 x 348	
TRS-112HN	Mid-high	HF	16	80 / 320 W	127 / 133 dB	125 Hz - 20 kHz	H. 30° to 40° V. 5° to 25°	32	580 x 568 x 450
		Mid	8	500 / 2000 W	129 / 135 dB				
TRS-212	Full range	4	625 / 2500 W	134 / 140 dB	80 Hz - 20 kHz	60° x 40°	54	946 x 568 x 445	
TRS-218	Subwoofer	4	1250 / 5000 W	135 / 141 dB	30 Hz - 300 Hz	Omni	105	576 x 1156 x 746	
TRS-Active	Subwoofer	4	1250 / 5000 W	135 / 141 dB	30 Hz - 300 Hz	Omni	105	576 x 1156 x 746	
INFRA-SUB	Subwoofer	4	2400 / 9600 W	135 / 141 dB	24 Hz - 45 Hz	Omni	96	576 x 1156 x 900	

*Dependant on array design

** Rotational horn

Active Cabinets

Active Model	Type	Power Peak (dB)	MAX SPL Peak	Freq Resp (-3dB)	Dispersion	Weight (kgs)	Dimensions H x W x D (mm)
Active Monitor	Full range	LF 400 W + HF 400 W	129 dB	60 Hz - 20 kHz	60° x 40°	23.5	418.5 x 500 x 464.5
Active-13	Full range	LF 400 W + HF 400 W	129 dB	60 Hz - 20 kHz	60° x 40°	23.5	556 x 410 x 350
Active Sub	Subwoofer	800 W	131 dB	45 Hz - 105 Hz	Omni	34.8	758.5 x 525 x 450
VLA Active Top 4 Ohm	Mid-high	400 W	126 dB	200 Hz - 20 kHz	10° x 70°	13	1000 x 160 x 160
VLA Sub	Subwoofer	400 W	126 dB	50 Hz - 250 Hz	Omni	32	1000 x 250 x 380

As part of our continuous R & D programme, **OHM(UK)LTD** reserves the right to change the specifications without prior notice. E. & O. E.

serious about sound