

STICK Rang

	STICK-GU2 128 channels	STICK-GA2 512 channels	STICK-DE3 1024 channels	STICK-KE1 1024 channels
Design	Glass	Glass	Glass	Plastic
Dimensions	86 x 86 x 11 mm	86 x 110 x 11 mm	106 x 146 x 11 mm	130 x 170 x 11 mm
Weight	130g	160g	250g	200g
USB connection	•	•	•	•
Ethernet connection			•	•
DMX channels	128	512	2x512	2x512
Easy Stand Alone software (PC)	•			•
Easy Stand Alone 2 software (PC/Mac)	•	•	•	•
ESA Pro software (PC)			•	•
DMX Recorder software			•	
Sunlite Suite 2 Software (PC)			•	•
Easy View 3D Software (PC)	Limited mode	Limited mode	Full mode	Full mode
STICK Remote app (iOs / Android)			•	•
Arcolis app (iOs / Android)			•	•
Number of scenes	24	99	500	200
Number of zones	1	1	10	5
Stand Alone memory	12K	76K	microSD	microSD
Memory capacity (steps) with 20 channels	842	3200	SD Card Limit	SD Card Limit
Memory capacity (steps) with 60 channels	311	1200	SD Card Limit	SD Card Limit
Memory capacity (steps) with 512 channels		140	SD Card Limit	SD Card Limit
Power voltage	5-12V DC 300mA 5.5v max with USB	5-12V DC 300mA 5.5v max with USB	5-6V DC 300mA 5.5v max with USB	5-10V DC 300mA 5.5v max with USB
Power connector	Screw Terminal	Screw Terminal or RJ45	Screw Terminal or RJ45	Screw Terminal
Live Control	Color, Dimmer	Color, Dimmer	Color, Dimmer, Speed	Color, Dimmer, Speed
touch-sensitive buttons	3	4	10	15
Port triggering	1	8 (255 in binary)	8 (255 in binary)	8 (255 in binary)
Clock triggering			100	40
RS232 triggering			•	•
Audio triggering				KU1 Only
Infra Red triggering				•
AC/DC adapter	Accessory POWER4M	Accessory POWER4M	Accessory POWER4M	Accessory POWER4M
Infrared remote control				Accessory IR-REMOTE
RJ45 to CONNECTOR BLOCK board			Accessory RJ2BLOCK	

SLESA Range

	SLESA-IP1 IP Version	SLESA-U9 Entry level USB	SLESA-U8 USB Version	SLESA-UE7 USB Ethernet SD Version
Windows XP/Vista/Seven	32/64-bit	32/64-bit	32/64-bit	32/64-bit
USB connection		•	•	•
Ethernet connection	•			•
Internet connection	•			
DMX Recorder software (PC)				•
Easy Stand Alone software (PC)	•	•	•	•
Easy Stand Alone 2 software (PC/Mac)		•	•	•
ESA Pro software (PC)				•
Sunlite Suite 2 Software (PC)				
Easy View 3D Software (PC)	Limited Mode	Limited Mode	Limited Mode	Limited Mode
DMX channels	512	256	512	2x512
Number of scenes	255	20	99	250
Number of zones	1	1	1	5
Stand Alone memory	32K	20K	128K	microSD
Memory capacity (steps) with 20 channels	5629	1184	7677	Unlimited
Memory capacity (steps) with 60 channels	2109	439	2877	Unlimited
Memory capacity (steps) with 512 channels	259		355	Unlimited
Power voltage	9V DC 300mA	5-5.5V DC 300mA Up to 16v with external power (not USB)	5-5.5V DC 300mA	5-5.5V DC 300mA
Power connector	Round 2,1mm	mini USB	mini USB	mini USB
Mechanical buttons	3	3	3	3
touch-sensitive buttons				
Internal HE10 extensions connector			•	•
Ports triggering	8	8	8	8
Clock triggering	20 (not astronomical)		100	40
RS232 triggering				
Audio triggering				
Infrared remote control				•
WIFI smartphone remote control				•