




**Fohhn**  
colors of sound


Datasheet

# X Series XT-22



## X Series XT-22

The XT-22 is a lightweight passive speaker for mobile use. Like all tops in the X series, it delivers first-class sound as a fullrange speaker, stage monitor, nearfill or in a system with Fohhn subwoofers. The sturdy enclosure, made of multiplex birch plywood with durable paintwork, is designed for tough days on the road.



- Equipped with: 10" / 1"
- Electronic high frequency protection
- Nominal power rating: 300 watts
- Nominal impedance: 8 ohms
- SPL max.: 127 dB
- Dispersion: 90° × 60° (H × V)
- Connections: 2 × Speakon
- Built-in flange mount and safety eyebolt
- Available in RAL Classic, NCS or Pantone colours on request
- Optionally available with weatherproof PU coating
- Versatile accessories for mobile use
- In order to ensure performance and operational safety, Fohhn system amplifiers including the correct speaker preset are required.



Available with the following color options



Equipped with the following Fohhn technologies



# Technical data

## Electroacoustic features

acoustic design	passive loudspeaker, 2-ways, rotatable Constant Directivity Horn
power rating (nominal)	300 watts
power rating (peak)	600 watts
components	10" / 1" CD, fully neodymium, time-aligned
sensitivity	99 dB
maximum SPL	127 dB
frequency range	65 Hz – 20 kHz
nominal impedence	8 ohms
nominal dispersion (h × v)	90° × 60°

## Physical features

enclosure	multiplex birch plywood
connectors	2 × Speakon
dimensions (w × h × d)	ca. 320 × 510 × 290 mm
angle for monitor set-up	55°
speaker stand pole	integrated, Ø 36 mm
weight	approx. 13 kg
standard colors	textured paint, black
handles	2 edge handles
EN 54-24	no
front design	acoustic foam
protection grille	steel grille, ball impact resistant, powder coated
mounting points	mounting threads for U-bracket, safety-eyelet on the back

## Optional features

special colors	RAL Classic / NCS / Pantone on request
optional weather protection	polyurethane coating, water-repellent speaker cone impregnation

power rating (nominal/program): according to IEC-60268-5 (long term/short term)  
power rating (peak); maximum SPL: peak, 20 ms with bandpass filtered pink noise signal according to IEC 60268-2 at one octave above the lower limit of the frequency range, with speaker preset  
sensitivity: 2,83 V at 8 ohms (2 V at 4 ohms, 4 V at 16 ohms) at a distance of 1 m under anechoic fullspace conditions  
frequency range: -10 dB under anechoic halfspace-conditions with speaker preset  
weight: net weight without optional equipment  
nominal dispersion: -6 dB compared to the main dispersion axis

Fohhn Audio AG  
Großer Forst 15  
72622 Nürtingen  
Germany

Phone +49 7022 93323-0  
Fax +49 7022 93324-0  
[www.fohhn.com](http://www.fohhn.com)  
[contact@fohhn.audio](mailto:contact@fohhn.audio)



Fohhn Audio AG reserves the right to make changes to its product design and technology without notice. All information is subject to change.  
© 2026, Fohhn Audio AG, Germany.

Document version: 2026-01-29 12:20:39